

# Automatic Foam

شركة المصنع السعودي لأجهزة الإطفاء  
SAUDI FACTORY FOR FIRE EQUIPMENT Co.



## FX Matic Model



SFFECO Automatic Foam Extinguishing Installation Type model FX-Matic is the latest developed design where in the AFFF foam is automatically ejected through the sprinkler head after release of the thermo safety device on reaching a temperature of 68°C. (Alternative 79°C or 93°C).

The modular type of extinguishers are based on sprinkler technology. It does not require any external source of power to operate.

### Class of Fire



Solid matters forming glowing residues. e.g. wood, rubber (car tires), paper, textiles.



Liquid combustible matter e.g. petrol, oils, grease, ether, alcohol.

### CAUTION:

NOT FOR USE ON LIVE ELECTRICAL EQUIPMENT



Model	FX4.5 MATIC	FX6 MATIC	FX10 MATIC	FX12 MATIC	FX15 MATIC	FX20 MATIC	FX25 MATIC	FX30 MATIC
Capacity	4.5 Ltr	6 Ltr	10 Ltr	12 Ltr	15 Ltr	20 Ltr	25 Ltr	30 L
Total Weight	10.56 Kg	12.06 Kg	19 Kg	22.92 Kg	26 Kg	34 Kg	41 Kg	47 Kg
Total Height (mm)	400	400	460	485	555	525	470	575
Cylinder Height (mm)	162	162	280	305	370	340	320	390
Cylinder Diameter (mm)	280	280	280	280	280	360	360	360
Duration of Discharge (Sec)	20-28	25-30	50-60	60-90	90-120	120-150	150-180	180-210
Extinguishing Agent	AFFF							
Propelling Agent	N <sub>2</sub>							
Working Pressure (Bar)	12-15							
Testing Pressure (Bar)	30							
Coating	Electrostatic Polyester Powder							
Storage Temperature (°C)	5°C to 60°C							

In line with our policy of continuous product improvement, SFFECO reserves the right to modify specifications without prior notice.